

# Celxpert Safety Data Sheet

## [29 CFR 1910.1200]

### Safety Data Sheet

May be used to comply with OSHA’s Hazard communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

### US Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form) Form Approved  
OMB No.1218-0072

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME :** Lithium Ion Rechargeable Battery Pack

**CUSTOMER :** SRAM

**CUSTOMER P/N :** 29.3018.114.000

**CPT P/N :** 913300002

**MODEL NAME :** 25402

**DESCRIPTION :** Lithium Ion Rechargeable Battery Pack

**Capacity :** 300mAh (Typical)

**Power(Watt-Hour rating) :** 2.2Wh

**Net weight :** 23+/-2g

**MANUFACTURER :** Celxpert Energy Co., Ltd

**ADDRESS :** No.128, Gong Wu Rd., Wu Lin Vil., Lung Tan, Taoyuan, Taiwan, 325, R.O.C.

**TELEPHONE :** +886-3-4899054

**FAX :** +886-3-4897320

Celxpert contact window: Josh Sung For more information,call: +886-3-4899054

SRAM Emergency Call: +1 352-323-3500

## SECTION 2: HAZARDS IDENTIFICATION

### PROTENTIAL HEALTH EFFECTS

### PRIMARY ROUTES OF ENTRY

Skin contact, Skin absorption, Eye contact, Inhalation, and Ingestion : NO

**SYMPTOMS OF EXPOSURE**

Skin contact

No effect under routine handling and use.

Skin absorption

No effect under routine handling and use.

Eye contact

No effect under routine handling and use.

Inhalation

No effect under routine handling and use.

**SECTION 3: INGREDIENT**

Battery Cell

<b>HAZARDOUS INGREDIENTS</b>	<b>%</b>	<b>CAS NUMBER</b>
Cobalt compound	4-50	1307-96-6
Styrene-Butadiene-Rubber	<1	27288-99-9
Aluminum Foil	2-10	7429-90-5
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Copper Foil	2-10	7440-50-8
Carbon	10-30	7440-44-0
Electrolyte (Ethylene carbonate)	10-20	96-49-1
Lithium hexafluorophosphate	<5	21324-40-3
Stainless steel, Nickel and inert materials	Remainder	N/A

Circuit Module

<b>HAZARDOUS INGREDIENTS</b>	<b>%</b>	<b>CAS NUMBER</b>
Lead	0.001	7439-92-1
Mercury	0	7439-97-6
Chromium	0	7440-47-3
Cadmium	0	7440-43-9
Plastic case and Si2O	0	N/A

Plastic Parts and Paints

<b>HAZARDOUS INGREDIENTS</b>	<b>%</b>	<b>CAS NUMBER</b>
Lead	<0.1	7439-92-1
Nickle	<0.01	7440-02-0
CFCs	0	75-69-4
Polychlorinated Biphenyls	0	1336-36-3

**SECTION 4: FIRST AID MEASURES**

INHALATION, EYE CONTACT, and SKIN CONTACT : Not a health hazard.

#### INGESTION

If swallowed, obtain medical attention immediately.

If exposure to internal materials within cell(pack) due to damaged outer casing, the following actions are recommended.

#### INHALATION

Leave area immediately and seek medical attention.

#### EYE CONTACT

Rinse eyes with water for 15 minutes and seek medical attention.

#### SKIN CONTACT

Wash area thoroughly with soap and water and seek medical attention.

#### INGESTION

Drink milk/water and induce vomiting; seek medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 GENERAL HAZARD

Cell is not flammable but internal organic material will burn if the cell is incinerated.

Combustion products include, but are not limited to hydrogen fluoride, carbon monoxide and carbon dioxide.

### 5.2 EXTINGUISHING MEDIA

Use extinguishing media suitable for the materials that are burning.

### 5.3 SPECIAL FIREFIGHTING INSTRUCTIONS

If possible, remove cell(s) from fire fighting area. If heated above 125°C, cell(s) can explode/vent.

### 5.4 FIREFIGHTING EQUIPMENT

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full

protective gear.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 ON LAND**

Place material into suitable containers and call local fire/police department.

**6.2 IN WATER**

If possible, remove from water and call local fire/police department.

**SECTION 7: HANDLING AND STORAGE**

**7.1 HANDLING**

No special protective clothing required for handling individual cells.

**7.2 STORAGE**

Store in a cool, dry place.

**SECTION 8: EXPOSURE CONTROLS//PERSONAL PROTECTION**

**8.1 ENGINEERING CONTROLS**

Keep away from heat and open flame. Store in a cool dry place.

**8.2 PERSONAL PROTECTION**

Respirator: Not required during normal operations. SCBA required in the event of a fire.

Eye/face protection: Not required beyond safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State : Solid	Boiling point : N/A
Odor : N/A	Solubility in water : Insoluble
PH : N/A	Specific gravity : N/A

Vapor pressure : N/A	Density : N/A
Vapor density : N/A	Flash Point : N/A

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 REACTIVITY

None

### 10.2 INCOMPATIBILITIES

None during normal operation. Avoid exposure to heat, open flame, and corrosives.

### 10.3 HAZARDOUS DECOMPOSITION PRODUCTS

None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

### 10.4 CONDITIONS TO AVOID

Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

## SECTION 11: TOXICOLOGICAL INFORMATION

This product does not elicit toxicological properties during routine handling and use.

Sensitization: NO Teratogenicity: NO Reproductive toxicity:NO Acute toxicity: NO

This product does not contain any kinds of the following substances and halogen-type flame retardants including Chlorine and Bromide type harmful flame retardants which are listed in Appendix of TCO documents and relevant international ECO requirements:

Polybromated Biphenyls (PBB)  
Polybromated Diphenylethers (PBDE)  
Polychlorinated Biphenyls (PCBs)  
Polychlorinated Terphenyls(PCTs)  
Polychlorinated Paphthalene(PCN)  
Chlorinated Paraffins(C10-C13)  
Chlorofluorocarbons(CFCs)  
Polyvinyl Chloride(PVC)  
Carbon Tetrachloride

None of the following substances will be exposed, leaked, or emitted during transportation, storage or any operation and any temperature condition:

Chlorinated Fluorohydrocarbon (FCKW)

Acrylonitrile

Styrol

Phenol

Benzol

Mercury of greater than 0.0001 wt% for alkaline battery

Mercury of greater than 0.0005 wt% for other battery

Lithium content of greater than 0.5g/battery cell

Cadmium, lead, and other harmful heavy metal

And will comply with the regulation of 49 CFR (DOT regulation), International Air Transport Association (IATA), and Deuche Forschungsgemeinschaft (DFG) regarding concentrations of emitted substances.

This product does not contain mercury and cadmium.

Mercury content: N/A

Cadmium content: N/A

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

## SECTION 12: ECOLOGICAL INFORMATION

Some materials within the cell are bio-accumulative. Under normal conditions, these materials are contained and pose no risk to persons or the surrounding environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

Disposal should be in accordance with local, state or national legislation.

## SECTION 14: TRANSPORT INFORMATION

- The International Civil Aviation Organization (ICAO) Technical Instructions.
- The International Air Transport Association (IATA) Dangerous Goods Regulations (65th Edition, 2024). Packing instruction 965 Section IB、 II for Lithium Ion battery. (When shipping batteries “packed with” or “contained in” equipment, use packing instruction 966 or 967 as appropriate).
- The International Maritime Dangerous Goods (IMDG) Code , 2022 Edition ( Incorporating Amendment 41-22 ) with special provision 188 & 230.
- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries, ST-SG-AC10-11-Rev7(UN3480) .

## SECTION 15: REGULATORY INFORMATION

OSHA hazard communication standard (29 CFR 1910.1200)

Hazardous                       Non-hazardous

## SECTION 16: OTHER INFORMATION

Package if damaged: do not load or transport.